



GridLok 270

Soil Reinforcement

GridLok...The engineered choice in soil reinforcement

GridLok 270 geogrid is designed specifically for use in soil reinforcement applications. It is composed of high tenacity polyester yarns, PVC coated for added protection against most naturally occurring chemicals, biological agents, installation damage and for resistance to harmful ultraviolet exposure.

PROPERTY	VALUE
Wide Width Tensile Strength¹ (ASTM D6637)	2700 lb/ft
Creep Limited Strength (ASTM D5262)	1753 lb/ft
Long Term Design Strength² (NCMA 2009, Sands silts and clays)	1475 lb/ft
Molecular Weight (min) (GRI-GG8)	30,000 g/mol
Carboxyl End Group (CEG) Count (max) (GRI-GG7)	30 meq/kg
Roll size	6 ft x 300 ft. (200 sq-yds.)

RidgeRock Retaining Walls, LLC
PO Box 241233
Charlotte, NC 28224

Phone: 704-504-3358
Fax: 704-504-3038

www.ridge-rock.com

 **RidgeRock
Retaining Walls, LLC**

1) Minimum average roll values unless denoted otherwise.
2) LTDS = $T_{ult} / (RF_{creep} \times RF_{installation\ damage} \times RF_{durability})$ for sand, silt and clay soils.